

SERIE MARFIL

Serie Doméstica



Diseñado y fabricado en España  
Designed and made in Spain

## CARACTERÍSTICAS CONSTRUCTIVAS SOBREPONER

Caja fuerte autónoma de alto nivel de seguridad y fácil instalación.

### ESPECIFICACIONES:

Puerta y marco de acero de 10mm de espesor cortados a láser.

Paredes de 4mm de espesor cortados a láser.

Bisagras interiores de acero que permiten la apertura de la puerta 90°.

### CERRADURA:

Cerradura de seguridad a gorjas con llave de doble paletón y llave de emergencia.

Cerradura de código electrónico.

El cerramiento de la puerta se efectúa mediante cinco pestillos niquelados y robustamente guiados.

### LLAVE DE EMERGENCIA:

En caso de cualquier avería, daños por ataque al sistema electrónico, olvido de la clave caja podrá ser abierta, mediante la llave de emergencia, con el uso de la llave de apertura normal.



## CARACTERÍSTICAS EMPOTRAR

Caja fuerte de empotrar de alto nivel de seguridad y instalación profesional.

### ESPECIFICACIONES:

Puerta y marco de acero de 10mm de espesor cortados a láser.

Paredes de 2mm de espesor cortados a láser.

Bisagras interiores de acero que permiten la apertura de la puerta 90°.

### CERRADURA:

Cerradura de seguridad a gorjas con llave de doble paletón y llave de emergencia.

Cerradura de código electrónico.

El cerramiento de la puerta se efectúa mediante cinco pestillos niquelados y robustamente guiados.

### LLAVE DE EMERGENCIA:

En caso de cualquier avería, daños por ataque al sistema electrónico, olvido de la clave caja podrá ser abierta, mediante la llave de emergencia, con el uso de la llave de apertura normal.

OPCIONAL: posibilidad de incorporar buzón en parte superior.

## FREE STANDING SAFES

Free standing high security safes with easy installation.

### SPECIFICATIONS:

Door & Steel plate - 10mm thickness. Laser cut.

Wall thickness 4mm. Laser cut.

Interior steel bolts allow a 90 degree door opening.

### LOCK:

Security lock to lever with double bitted key.

Electronic code lock.

Door closure achieved by engaging five robustly guided nickel plated hinges.

### EMERGENCY KEY:

In the event of opening failure, damage due to electronic system attack or forgotten password, the safe can be opened with the use of the emergency key in tandem with the standard key.

## WALL SAFES

High security wall safes with professional installation.

### SPECIFICATIONS:

Door & Steel plate - 10mm thickness. Laser cut.

Wall thickness 2mm. Laser cut.

Interior steel bolts allow a 90 degree door opening.

### LOCK:

Security lock to lever with double bitted key.

Electronic code lock.

Door closure achieved by engaging five robustly guided nickel plated hinges.

### EMERGENCY KEY:

In the event of opening failure, damage due to electronic system attack or forgotten password, the safe can be opened with the use of the emergency key in tandem with the standard key.

OPTIONAL: mailbox slat on top of the safe.



## CAJA FUERTE DE SOBREPONER

### FREESTANDING

MODELO MODEL	APERTURA OPENING	EXTERIOR/EXTERIOR			INTERIOR/INTERIOR			BANDEJA SHELF	CAPACIDAD CAPACITY	PESO WEIGHT
		ALTO HEIGHT	ANCHO WIDTH	FONDO DEPTH	ALTO HEIGHT	ANCHO WIDTH	FONDO DEPTH			
H-320S	Derecha/Right	320	420	306	304	412	245	1	37 L.	36 Kg.
V-420S	Derecha/Right	420	385	306	404	377	245	2	30 L.	38 Kg.
V-520S	Derecha/Right	520	400	306	504	392	245	2	48 L.	52 Kg.
V-730S	Derecha/Right	730	450	306	714	442	245	3	76 L.	71 Kg.

## CAJA CON BUZÓN

### MAILBOX SAFE

BV-520S	Derecha/Right	520	385	300	400	375	245	2	35 L.	51 Kg.
---------	---------------	-----	-----	-----	-----	-----	-----	---	-------	--------

## DOBLE CUERPO

### DOUBLE STEEL BODY

H-730SD	Derecha/Right	730	450	307	638	424	243	2	66 L.	100 Kg.
---------	---------------	-----	-----	-----	-----	-----	-----	---	-------	---------

## CAJA FUERTE DE EMPOTRAR

### WALL SAFE

MODELO MODEL	APERTURA OPENING	EXTERIOR/EXTERIOR			INTERIOR/INTERIOR			BANDEJA SHELF	CAPACIDAD CAPACITY	PESO WEIGHT
		ALTO HEIGHT	ANCHO WIDTH	FONDO DEPTH	ALTO HEIGHT	ANCHO WIDTH	FONDO DEPTH			
H-300E	Derecha/Right	300	385	300	208	359	243	1	22 L.	18 Kg.
H-320E	Derecha/Right	320	420	300	228	394	243	1	25 L.	22 Kg.
H-400E	Derecha/Right	400	520	300	308	494	243	1	36 L.	37 Kg.
V-420E	Derecha/Right	420	315	300	328	289	243	1	25 L.	23 Kg.
V-420E*	Derecha/Right	420	385	300	328	359	243	1	29 L.	29 Kg.
V-520E	Derecha/Right	520	400	300	428	374	243	2	36 L.	39 Kg.
V-730E	Derecha/Right	730	450	300	638	424	243	2	52 L.	66 Kg.